according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EasyStart® Microfast BS 13-40-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Fertilizer

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : COMPO EXPERT GmbH

Krögerweg 10 D-48155 Münster

Telephone : +49 (0) 251 29 79 81 – 000

Telefax : +49 (0) 251 29 79 81 - 111

E-mail address of person

responsible for the SDS

: info@compo-expert.com

1.4 Emergency telephone number

GBK GmbH - Global Regulatory Compliance - 24h

Telephone: +49 (0) 6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting

effects.

Precautionary statements : **Disposal:**

P501 Dispose of contents/ container to an

approved waste disposal plant.

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 **Revision Date:** Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : NP - fertilizer contains:

N,N´-(2-Methylpropyliden)-bis-urea

methylene urea manganese sulphate

iron sulfate zinc oxide Bacillus subtilis

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
ammonium nitrate	6484-52-2 229-347-8 01-2119490981-27- XXXX	Ox. Sol. 3; H272 Eye Irrit. 2; H319	<= 10
manganese sulphate (1:1)	7785-87-7 232-089-9 01-2119456624-35- XXXX	STOT RE 2; H373 Aquatic Chronic 2; H411 Eye Dam. 1; H318	<= 2,3
zinc oxide	1314-13-2 215-222-5 01-2119463881-32- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 2,5

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Wash hands with water as a precaution.

If inhaled : Move to fresh air in case of accidental inhalation of fumes

from overheating or combustion.

Obtain medical attention.

In case of lung irritation, first treatment with dexametason

aerosol (spray).

In case of skin contact : Wash off with plenty of water.

In case of eye contact : Rinse thoroughly with plenty of water for at least 15 minutes

and consult a physician.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Ingestion may provoke the following symptoms:

Methaemoglobinemia

Inhalation of decomposition products in high concentration

may cause shortness of breath (lung oedema).

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water

Unsuitable extinguishing : Foam

media Dry chemical

Carbon dioxide (CO2)

Sand

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Can decompose at above 100 °C. Thermal decomposition

products:

Nitrogen monoxide, nitrogen dioxide, dinitrogenoxide,

ammonia Isobutyraldehyd

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 **Revision Date:** Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Keep away from children.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Retain and dispose of contaminated wash water.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

6.4 Reference to other sections

none

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Protect from contamination.

Keep away from direct sunlight.

Protect against heat. Protect from moisture.

Advice on protection against

fire and explosion

The product is not flammable. Keep away from sources of ignition - No smoking. Keep away from combustible materials.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Risk of explosion if heated

under confinement.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: When stored loose do not mix with other fertilizers. Store well away from other substances. Keep away from direct sunlight. Protect against heat. Protect from contamination. Protect from

moisture.

Storage class (TRGS 510) : 13, Non Combustible Solids

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 **Revision Date:** Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

Dampness : Keep in a dry place.

7.3 Specific end use(s)

Specific use(s) : Always read the label and product information before use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
manganese	manganese	(Inhalable	0,5 mg/m3	DE TRGS
sulphate (1:1)	sulphate	fraction)		900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., The threshold value is based on the element content of the corresponding metal., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Inhalable fraction)	0,5 mg/m3 (Manganese)	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., The threshold value is based on the element content of the corresponding metal., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
			0,5 mg/m3	
zinc oxide	1314-13-2		2 mg/m3	

Contains no substances wit	n occupational	exposure illilit values.	_	_
Mangansulfat	7785-87-7,	manganese: 20 μg/l	Immediately after	TRGS 903
	7785-87-7	(Blood)	exposition or after	
		(Diood)	working hours, In	
			case of long-term	
			exposition: after	
			more than one shift	
i	į		i	1

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	· · ·			
Substance name	End Use	Exposure routes	Potential health effects	Value
ammonium nitrate	Workers	Inhalation	Long-term systemic effects	36 mg/m3
	Workers	Skin contact	Long-term systemic effects	5,12 mg/kg bw/day

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7

Date of last issue: 23.12.2022

Date of first issue: 10.11.2016

Revision Date: 07.04.2023

	Consumers	Ingestion	Long-term systemic effects	2,56 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,9 mg/m3
	Consumers	Skin contact, Ingestion	Long-term systemic effects	2,56 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term exposure	5 mg/m3
	Workers	Ingestion	Long-term exposure, Systemic effects	0,8 mg/kg
	Workers	Skin contact	Long-term exposure, Systemic effects	83 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name		Environmental Compartment	Value	
ammonium nitrate		Sewage treatment plant	18 mg/l	
zinc oxide		Fresh water	0,0206 mg/l	
		Marine water	0,0061 mg/l	
Remarks: Derivation		of the PNEC, Zinc		
		Fresh water sediment	235,6 mg/l	
	Derivation	of the PNEC, Zinc		
		Marine sediment	113 mg/l	
	Derivation	n of the PNEC, Zinc		
		Soil	106,8 mg/l	
	Derivation of the PNEC, Zinc			
	•	Behaviour in waste water treatment plants	0,052 mg/l	
Derivation of the PNEC, Zinc				

8.2 Exposure controls

Personal protective equipment

Eye protection : In case of dust formation:

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

Tightly fitting safety goggles

Hand protection

Material : Gloves

Skin and body protection : No special protective equipment required.

Respiratory protection : respiratory protection only if aerosol or dust is formed.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

Retain and dispose of contaminated wash water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : granular

Colour : various

Odour : odourless

Odour Threshold : No data available

pH : ca. 6,2, Concentration: 100 g/l (20 °C)

Melting point/range : No data available

Boiling point/boiling range : Not applicable

Flash point : Not relevant

Evaporation rate : Not applicable

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Bulk density : ca. 860 kg/m³

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: Not applicable

Auto-ignition temperature : Not applicable

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : Not applicable

Particle characteristics

Particle Size Distribution : D50 = 1,2 mm

D50 Tolerance range = 0,9 mm - 1,5 mm

Measurement technique: Optoelectronic measurement

method

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

Decomposes on heating.

10.3 Possibility of hazardous reactions

Hazardous reactions : Evolution of ammonia under influence of alkalies.

10.4 Conditions to avoid

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

Conditions to avoid : Keep away from heat and sources of ignition.

10.5 Incompatible materials

Materials to avoid : oxidizable substances

Strong acids and strong bases

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Nitrogen monoxide, nitrogen dioxide, dinitrogenoxide,

ammonia

Isobutyraldehyd

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Health injuries are not known or expected under normal use.

Acute dermal toxicity : Remarks: No data available

Health injuries are not known or expected under normal use.

Components:

ammonium nitrate:

Acute oral toxicity : LD50 (Rat): > 2.950 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : > 88,8 mg/l

Method: No information available.

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 402

manganese sulphate (1:1):

Acute oral toxicity : LD50 (Rat): 2.150 mg/kg

zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : Remarks: No data available

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

Skin corrosion/irritation

Product:

Result: non-irritant

Remarks: The product has not been tested. The information is derived from the properties of the

individual components.

Components:

ammonium nitrate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: non-irritant

zinc oxide:

Remarks: non-irritant

Serious eye damage/eye irritation

Product:

Species: Rabbit

Method: OECD Test Guideline 405

Result: non-irritant

Remarks: The product was not tested. The statement was derived from products of similar

structure and composition.

Components:

ammonium nitrate:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irritant

zinc oxide:

Method: OECD Test Guideline 405

Remarks: non-irritant

Respiratory or skin sensitisation

Product:

Result: non-sensitizing

Remarks: The product has not been tested. The information is derived from the properties of the

individual components.

Components:

ammonium nitrate:

Result: Does not cause skin sensitisation.

zinc oxide:

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

Method: OECD Test Guideline 406

Remarks: Did not cause sensitisation on laboratory animals.

germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Components:

ammonium nitrate:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Result: negative

zinc oxide:

Germ cell mutagenicity-

Assessment

: In vivo tests did not show mutagenic effects

Carcinogenicity

Product:

Remarks: Contains no ingredient listed as a carcinogen

Components:

ammonium nitrate:

Species: Rat

Remarks: Animal testing did not show any carcinogenic effects.

zinc oxide:

Carcinogenicity - : According to experience not expected

Assessment

Reproductive toxicity

Product:

Effects on fertility

Remarks: No toxicity to reproduction

The product has not been tested. The information is derived

from the properties of the individual components.

Components:

ammonium nitrate:

Effects on fertility : Species: Rat

Remarks: Animal testing did not show any effects on fertility.

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

Effects on foetal : Species: Rat

development Remarks: Did not show teratogenic effects in animal

experiments.

zinc oxide:

Reproductive toxicity - : No toxicity to reproduction

Assessment No experimental indication of genotoxic effects.

STOT - single exposure

Product:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single

Remarks: The product has not been tested. The information is derived from the properties of the individual components.

Components:

zinc oxide:

Remarks: This information is not available.

STOT - repeated exposure

Product:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Remarks: The product has not been tested. The information is derived from the properties of the individual components.

Components:

zinc oxide:

Remarks: No known effect.

Repeated dose toxicity

Components:

ammonium nitrate:

Species: Rat

NOAEL: > 1.500 mg/kg Application Route: Oral Exposure time: 28 d

Species: Rat

NOAEL: = 256 mg/kg Application Route: Oral Exposure time: 52 w

Method: OECD Test Guideline 453

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 **Revision Date:** Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

Species: Rat

NOAEL: >= 185 mg/kg

Application Route: by inhalation

Exposure time: 2 w

Method: Repeated Dose Inhalation Toxicity: 28-day or 14-day Study.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

No data available

Further information

Product:

Remarks: Danger of methaemoglobin formation.

The product was not tested. The statement was derived from products of similar structure and

composition.

SECTION 12: Ecological information

12.1 Toxicity

Product:

: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: Directive 84/449/EEC, C.2

Toxicity to algae : EC50 (Scenedesmus subspicatus): > 100 mg/l

Exposure time: 72 h Method: DIN 38412

Components:

ammonium nitrate:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

: EC50 (Daphnia (water flea)): 490 mg/l aquatic invertebrates

Exposure time: 48 h

LC50: 490 mg/l

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 1.700 mg/l

Exposure time: 10 d

manganese sulphate (1:1):

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 30 mg/l

zinc oxide:

Toxicity to fish : LC50 (Fish): 0,14 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 2,2 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 0,17 mg/l

Exposure time: 72 h Test Type: static test

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical : DOC reduction

removability ca. 85 %

Method: OECD 301E/92/69/EWG, C.4-B Remarks: Readily eliminated from water

Components:

ammonium nitrate:

Biodegradability : Remarks: The methods for determining the biological

degradability are not applicable to inorganic substances.

zinc oxide:

Biodegradability : Remarks: The methods for determining biodegradability are

not applicable to inorganic substances.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Components:

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

ammonium nitrate:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

: log Pow: -3,1

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among : Remarks: Moderately mobile in soils

environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : Remarks: Not applicable

Components: zinc oxide:

Assessment : Non-classified PBT substance.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological

information

: Inhibition of degradation activity in activated sludge is not to

be anticipated during correct introduction of low

concentrations.

There is a high probability that the product is acute not

harmful to aquatic organisms.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Check if agriculture use is possible.

Contact manufacturer.

Contaminated packaging : Contaminated packaging should be emptied as far as

possible; then it can be passed on for recycling after being

thoroughly cleaned.

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

SECTION 14: Transport information

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class

(Germany)

: WGK 1 slightly water endangering

Other regulations : This product is subject to Regulation (EU) 2019/1148;

suspicious transactions, disappearance or theft of the product

must be reported to the relevant authority.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this product.

SECTION 16: Other information

Full text of H-Statements

H272 : May intensify fire; oxidizer.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date:
Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Acute aquatic toxicity
Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Ox. Sol. : Oxidizing solids

STOT RE : Specific target organ toxicity - repeated exposure

(Q)SAR - (Quantitative) Structure Activity Relationship; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ASTM -American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation: Regulation (EC) No 1272/2008; DIN - Standard of the German Institute for Standardisation: ECHA - European Chemicals Agency; EC-Number - European Community number: ECx - Concentration associated with x% response: ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TRGS - Technical Rule for Hazardous Substances; UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative; DSL - Domestic Substances List (Canada); KECI - Korea Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); AICS -Australian Inventory of Chemical Substances; IECSC - Inventory of Existing Chemical Substances in China; ENCS - Existing and New Chemical Substances (Japan); ISHL - Industrial Safety and Health Law (Japan); PICCS - Philippines Inventory of Chemicals and Chemical Substances; NZIoC - New Zealand Inventory of Chemicals; TCSI - Taiwan Chemical Substance Inventory; CMR - Carcinogen, Mutagen or Reproductive Toxicant; GLP - Good Laboratory Practice

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

Material Safety Data Sheet according to Regulation (EC) No. 1907/2006

EasyStart® Microfast BS 13-40-0



Version: 1.7 Revision Date: Date of last issue: 23.12.2022 07.04.2023

Date of first issue: 10.11.2016

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN